



16	54-72505-00	Self-tapping self-drilling screws	ST6. 3-12	16
15	03-66197-00	Support plate2	&=2. 0 Q235 steel plate	2
14	03-66196-00	Support plate1	&=2. 0 Q235 steel plate	2
13	01-65011-00	Shock absorber pad	1. 97-1. 97-0. 20	4
12	54-30308-00	Stainless steel nut	3/8	4
11	54-40308-00	Stainless steel spring washer	3/8	4
10	54-50308-00	Stainless steel flat washer	3/8-0. 83-0. 08	8
9	54-60308-11	Stainless steel bolt	3/8-16-1. 5	4
8	54-30516-01	Stainless steel cap nut	5/16	28
7	54-40516-00	Stainless steel spring washer	5/16	28
6	54-50516-00	Stainless steel flat washer	5/16-0. 63-0. 04	32
5	54-60516-34	Stainless steel bolt	5/16-18-3/4	4
4	03-66195-00	Mounting bracket	&=2. 0 Q235 steel plate	2
3	03-66194-00	Longitudinal beam (width)	&=2. 0 Q235 steel plate	2
2	03-66193-00	Longitudinal beam (Length)	&=2. 0 Q235 steel plate	2
1	66-60619-00	Column assembly	Welded component	4
#	Part Number	Name	Description	Number

Description:

- 1 • Design reference standard: GB/T 35753-2017
- 2 • Corrosion resistance reference ASTM-B117 500 hours;
- 3 • Surface powder-coated gray (RAL7035), ≥85um;
- 4 • Air conditioner foot position range:  
Length: 309mm--787mm [12. 17"--30. 98"];  
Width: 279mm--579mm [10. 98"--22. 80"];
- 5. Design rated load capacity: 453.6Kg [1000 lbs];
- 6. Units not specified are in metric.

					Assembly				Shi Zun Metal	
									Air Conditioner Mounting Bracket	
									BRKH422418	
Mark	Number of Places	Change File Number	signature	Date	Stage Marking	Base Number	Weight (Kg)	Scale		
Design		Process				1	22. 12	1:12		
Drafting		Standardization								
Proofreading		Version	1		Total Page:1		Page:1			
Review		Approval								