



## Submittal-60K-UltraniXX

Job name:		Submitted by:	
Location:		Submitted to:	
Engineer:		Unit tag:	
Date:		Drawing number:	

### Warranty information

Standard 7 years parts & compressor  
Registered 12 years parts & compressor  
Terms and conditions apply

### Type

Energy Star Heat Pump ☐  
Cold Climate Energy Star Heat Pump ☐

### Model numbers

Indoor: KCAC60H/NHA

Outdoor: KU60UXO

### Capacity range

Output (BTU/H)	Minimum	Rated	Max	Certification		
Cooling:	15200	52000	53100	AHRI NO.	Energy Star	nep
Heating:	14400	53000	53600	217052380		

### Heating performance

Output (BTU/H)	Minimum	Rated	Max	Efficiency Ratings	
47F (8.3C)	14400	53000	53600	SEER2	15.2
17F (-8.3C)	7800	35200	35600	HSPF2	8.5
5F (-15C)	18900	40000	40000	EER (W/W)	2.8
				COP (W/W)	2.9

### Outdoor temperature range


Cooling:	-15-54C	5-129F	Electrical	
Heating:	-30-24C	-22-75F	Power supply	208-230V/60Hz/1Ph
			Min/Max voltage	187-253Vac

### Condenser specifications

Connecting type	Screw Connection	MCA	39A
Pre-charge length	25ft (7.5M)	MOP	45A
MIN. Refrigerant Pipe Length	10 ft (3M)	Power Supply Wire	8/3 AWG
		Interconnecting Wire	18/6AWG or 18/2AWG

Liquid Pipe Size	3/8in (9.52mm)	Features:	
Gas Pipe Size	3/4in (19mm)	Electronic expansion valve	
Max Height Between Indoor/Outdoor	50ft (15M)	Rotary compressor	
Max. Pipe Length	100ft (30M)	Basepan heater	
Refrigerant Type	R-32	Compressor electric heater	

Factory Charge	162oz	Weight	
Additional Charge	0.3 oz/ft	Gross weight:	263.5Lbs (119.5Kg)
Sound Pressure Level	62dB (A)	Net weight:	241.4Lbs (109.5Kg)



R32




Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.




# Outdoor Unit Dimensions

KU60UXO



Minimum outdoor unit clearances



Unit must be placed a minimum 18in (45cm) above any surfaces to allow for snow clearance and defrost runoff.

Please follow local best practices and guidelines.


Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.





# Indoor Unit Specifications

KCAC60H/NHA


Move to the left:



Move to the right:



Control board can be moved according to installation needs

Optional Smart thermostat		Technical Specifications	
		Power Supply	24V/60Hz/1Ph
		Throttling method	Electronic Expansion Valve
		Connection method	Screwed
		Liquid pipe size	3/8in (9.52mm)
		Gas pipe size	3/4in (19mm)
		Net weight	110 lbs (50Kg)
		Gross Weight	123.5 Lbs (56Kg)
		Drain Pipe Outlet	SCH 40 3/4
		Includes R32 Refrigerant Sensor	
		Can be installed horizontally	

Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.