



## Submittal-Airy 12K Minisplit

Job name:		Submitted by:	
Location:		Submitted to:	
Engineer:		Unit tag:	
Date:		Drawing number:	

Warranty information					
Standard 7 years parts & compressor					
Registered 12 years parts & compressor					
Terms and conditions apply					
Type					
Energy Star Heat Pump <input type="radio"/>					
Cold Climate Energy Star Heat Pump <input checked="" type="radio"/>					
Model numbers					
Indoor:	KW12XQ29S1DI				
Outdoor:	KW12XQ29S1DO				
Capacity range					
Output (BTU/H)	Minimum	Rated	Max	Certification	
Cooling:	2900	12000	17060	AHRI NO.	Energy Star
Heating:	3070	12200	18766	217903558	4514303
neep					
Heating performance					
Output (BTU/H)	Minimum	Rated	Max	SEER2	29.5
47F (8.3C)	3270	12200	18766	HSPF2	10
17F (-8.3C)	2800	13000	13000	EER (W/W)	4.4
5F (-15C)	2600	12200	12200	COP (W/W)	4.5
Outdoor temperature range					
Cooling:	-29-50C	-20-122F	Power supply	208-230V/60Hz/1Ph	
Heating:	-30-30C	-22-86F	Min/Max voltage	187-253Vac	
Condenser specifications					
Connecting type	Screw Connection	MOP	15A		
Liquid line size	1/4in (6mm)	Power Supply Wire	14/3 AWG		
Gas line size	1/2in (12mm)	Interconnecting Wire	14/4 AWG		
pre-charge length	24.6ft (7.5M)	Features:			
MIN. Refrigerant Pipe Length	10 ft (3M)	Electronic expansion valve			
MAX. Refrigerant Pipe Length	100 ft (30M)	Rotary compressor			
MAX. Vertical Height difference (total)	60 ft (20M)	Basepan heater			
Refrigerant Type	R-32	Compressor electric heater			
Factory Charge	35oz	Weight			
Additional Charge	0.2 oz/ft	Gross weight:	84.9Lbs (38.5Kg)		
Sound Pressure Level	55dB (A)	Net weight:	78.3Lbs (35.5Kg)		




Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.




# Outdoor unit Dimensions

KW12XQ29SDO



## Minimum outdoor unit clearances



Unit must be placed a minimum 18in (45cm) above any surfaces to allow for snow clearance and defrost runoff.

Please follow local best practices and guidelines.

Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.



# Indoor unit specifications

KW12XQ29SDI			
Air flow volume		dB (A)	
Turbo	565 CFM	960 m3/h	43
High	506 CFM	860 m3/h	42
Med-high	477 CFM	810 m3/h	40
Medium	441 CFM	750 m3/h	39
Med-low	406 CFM	690 m3/h	33
Low	371 CFM	630m3/h	29
Sleep	353 CFM	600 m3/h	27


Net weight:	33.1 Lbs 15 Kg	Gross weight:	38.6 Lbs 17.5 Kg
Included:	Infrared remote YBE1FBF		
Dehumidification level:	2.96 pt/hr		
Optional Accessories			
24V interlock wired controller:	XE71-00/E		
Wired controller:	XE71-44G		
Embedded wired controller:	XE74-44E		
Embedded WIFI wired controller	XE72-44E		

## Included Features


WI-FI control | 8C heating | I-feel | Self clean | Forced defrost | Soft start | Low voltage startup

## Indoor unit Dimensions

Unit: mm(inch)



## Minimum indoor unit clearances



Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.