



Submittal-48K-Ultranixx

Job name:		Submitted by:	
Location:		Submitted to:	
Engineer:		Unit tag:	
Date:		Drawing number:	

Warranty information	
Standard 7 years parts & compressor	
Registered 12 years parts & compressor	
Terms and conditions apply	
Type	
Energy Star Heat Pump <input type="radio"/>	
Cold Climate Energy Star Heat Pump <input checked="" type="radio"/>	
Model numbers	
Indoor:	KD48UXI
Outdoor:	KU60UXO
Capacity range	




Output (BTU/H)	Minimum	Rated	Max	Certification					
Cooling:	34000	48000	50000	AHRI NO.	Energy Star	neep			
Heating:	34000	48000	52000	217194946	4,011,419.				
Heating performance					Efficiency Ratings				
Output (BTU/H)	Minimum	Rated	Max	SEER2	17				
47F (8.3C)	15800	48000	48400	HSPF2	9.5				
17F (-8.3C)	9800	39500	41500	EER (W/W)	3.3				
5F (-15C)	18600	48000	48000	COP (W/W)	3.3				
Outdoor temperature range					Electrical				
Cooling:	-15-54C	5-129F		Power supply	208-230V/60Hz/1Ph				
Heating:	-30-24C	-22-75F		Min/Max voltage	187-253Vac				
Condenser specifications					MCA	39A			
Connecting type	Screw Connection		MOP	45A					
Pre-charge length	25ft (7.5M)		Power Supply Wire	8/3 AWG					
MIN. Refrigerant Pipe Length	10 ft (3M)		Interconnecting Wire	18/6AWG or 18/2AWG					
Liquid Pipe Size	3/8in (9.52mm)		Features:						
Gas Pipe Size	3/4in (19mm)		Electronic expansion valve						
Max Height Between Indoor/Outdoor	50ft (15M)		Rotary compressor						
Max. Pipe Length	100ft (30M)		Basepan heater						
Refrigerant Type	R-32		Compressor electric heater						
Factory Charge	162oz		Weight						
Additional Charge	0.3 oz/ft		Gross weight:	263.5Lbs (119.5Kg)					
Sound Pressure Level	62dB (A)		Net weight:	241.4Lbs (109.5Kg)					


Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.



Outdoor unit Dimensions



Minimum outdoor unit clearances



Unit must be placed a minimum 18in (45cm) above any surfaces to allow for snow clearance and defrost runoff.

Please follow local best practices and guidelines.

Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.



Indoor unit specifics

KD48UXI

Unit: Inch



Technical Specifications	
Power Supply	208-230V/60Hz/1Ph
Sound pressure level	53dB(A)
MCA	7.1A
MOC	15A
Dehumidification	8.49 pt/hr
Net weight	199.5 lbs (90.5Kg)
Gross Weight	218 Lbs (99Kg)
Drain Pipe Outlet	SCH 40 3/4
*When there is no Electrical Heater installed There is no supplied Electrical breaker	
*If Electrical Heater is installed it will supply power to air handler	

Optional Smart thermostat	Electric Heater kits available					
WK-010WC01 and WK-010WD1	Model number	KW	MCA 240V	MCA 208V	MOC 240V	MOC 208V
* Metal mesh filter included	21-4216-03	10	52A	45A	60A	45A
20 5/8 x 20 5/16 x 1/2	21-4217-01	15	52A & 26A	45A & 22.6A	60A & 30A	45A & 25A
Fan Performance	21-4228-01	20	52A & 52A	45A & 45A	60A & 60A	45A & 45A

Level	Static pressure:inwg (Pa)											
	0 (0)	0.1 (25)	0.15 (37)	0.2 (50)	0.3 (75)	0.4 (100)	0.5 (125)	0.6 (150)	0.7 (175)	0.8 (200)	0.9 (225)	1 (250)
Speed 1(CFM)	1680	1560	1500	1350	-	-	-	-	-	-	-	-
Speed 2(CFM)	1810	1690	1620	1550	1380	-	-	-	-	-	-	-
Speed 3(CFM)	1930	1830	1770	1710	1580	1480	1200	-	-	-	-	-
Speed 4(CFM)	2280	2240	2200	2180	2130	2080	2000	1880	1750	1600	1400	1200
Speed 5(CFM)	2300	2260	2220	2190	2140	2090	2040	1980	1930	1800	1700	1550

Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.