



Submittal-Clivia 12K Minisplit

Job name:		Submitted by:	
Location:		Submitted to:	
Engineer:		Unit tag:	
Date:		Drawing number:	

Warranty information

Standard 7 years parts & compressor
 Registered 12 years parts & compressor
 Terms and conditions apply

Type

Energy Star Heat Pump
 Cold Climate Energy Star Heat Pump

Model numbers

Indoor: KW12XQ25S1DI
 Outdoor: KW12XQ25S1DO

Capacity range



R32

20 Inverter



AHRI


Output (BTU/H)	Minimum	Rated	Max	Certification		
Cooling:	2730	12000	15013	AHRI NO.	Energy Star	nep
Heating:	3071	12000	15695	217933620	4,518,153.	
Heating performance				Efficiency Ratings		
Output (BTU/H)	Minimum	Rated	Max	SEER2	24.5	
47F (8.3C)	3070	12000	14600	HSPF2	9.5	
17F (-8.3C)	2700	7700	12000	EER (W/W)	3.8	
5F (-15C)	2600	11000	11000	COP (W/W)	3.8	
Outdoor temperature range				Electrical		
Cooling:	-29-50C	-20-122F		Power supply	208-230V/60Hz/1Ph	
Heating:	-30-30C	-22-86F		Min/Max voltage	187-253Vac	
Condenser specifications				MCA	10A	
Connecting type		Screw Connection		MOP	15A	
Liquid line size		1/4in (6mm)		Power Supply Wire	14/3 AWG	
Gas line size		1/2in (12mm)		Interconnecting Wire	14/4 AWG	
pre-charge length		24.6ft (7.5M)		Features:		
MIN. Refrigerant Pipe Length		10 ft (3M)		Electronic expansion valve		
MAX. Refrigerant Pipe Length		100 ft (30M)		Rotary compressor		
MAX. Vertical Height difference (total)		60 ft (20M)		Basepan heater		
Refrigerant Type		R-32		Compressor electric heater		
Factory Charge		28oz		Weight		
Additional Charge		0.2 oz/ft		Gross weight:	77.2Lbs (35Kg)	
Sound Pressure Level		52dB (A)		Net weight:	71.7Lbs (32.5Kg)	

Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.




Outdoor unit Dimensions

KW12XQ25S1DO



Minimum outdoor unit clearances



Unit must be placed a minimum 18in (45cm) above any surfaces to allow for snow clearance and defrost runoff.

Please follow local best practices and guidelines.

Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.



Indoor unit specifications

KW12XQ25S1DI


Air flow volume			dB (A)
Turbo	400 CFM	680 m3/h	43
High	365 CFM	620 m3/h	38
Med-high	330 CFM	560 m3/h	36
Medium	288 CFM	490 m3/h	34
Med-low	265 CFM	450 m3/h	32
Low	247 CFM	420 m3/h	30
Sleep	230 CFM	390 m3/h	25

Net weight:	20.9 Lbs	Gross weight:	25.4 Lbs
	9 Kg		11.5 Kg
Included:	Infrared remote YBE1FBB		
Dehumidification level:	2.96 pt/hr		
Optional Accessories			
24V interlock wired controller:	XE71-00/E		
Wired controller:	XE71-44G		
Embedded wired controller:	XE74-44E		
Embedded WIFI wired controller	XE72-44E		


Included Features

WI-FI control	8C heating	I-feel	Self clean	Forced defrost	Soft start	Low voltage startup
---------------	------------	--------	------------	----------------	------------	---------------------

Indoor unit Dimensions



Minimum indoor unit clearances



Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.