



Submittal-Clivia 12K Console

Job name:		Submitted by:	
Location:		Submitted to:	
Engineer:		Unit tag:	
Date:		Drawing number:	

Warranty information

Standard 7 years parts & compressor
Registered 12 years parts & compressor
Terms and conditions apply

Type

Energy Star Heat Pump

Cold Climate Energy Star Heat Pump

Model numbers

Indoor: KM12XEDI

Outdoor: KW12XQ25S1DO

Capacity range

Output (BTU/H)	Minimum	Rated	Max	Certification		
Cooling:	2700	12000	13300	AHRI NO.	Energy Star	nep
Heating:	3070	12000	14000	218451510		

Heating performance

Output (BTU/H)	Minimum	Rated	Max	Efficiency Ratings	
47F (8.3C)	3070	12000	14000	SEER2	23
17F (-8.3C)	2700	10000	12000	HSPF2	9
5F (-15C)	2600	10000	10000	EER (W/W)	3.8
				COP (W/W)	3.8

Outdoor temperature range

Cooling:	-29-50C	-20-122F	Electrical	
Heating:	-30-30C	-22-86F	Power supply	208-230V/60Hz/1Ph
			Min/Max voltage	187-253Vac

Condenser specifications

Connecting type	Screw Connection	MCA	10A
Liquid line size	1/4in (6mm)	MOP	15A
Gas line size	1/2in (12mm)	Power Supply Wire	14/3 AWG
pre-charge length	24.6ft (7.5M)	Interconnecting Wire	14/4 AWG

MIN. Refrigerant Pipe Length	10 ft (3M)	Features:	
MAX. Refrigerant Pipe Length	100 ft (30M)	Electronic expansion valve	
MAX. Vertical Height difference (total)	60 ft (20M)	Rotary compressor	
Refrigerant Type	R-32	Basepan heater	
Factory Charge	28oz	Compressor electric heater	
Additional Charge	0.2 oz/ft	Weight	
Sound Pressure Level	52dB (A)	Gross weight:	77.2Lbs (35Kg)
		Net weight:	71.7Lbs (32.5Kg)



R32

20 Inverter




AHRI




Outdoor unit Dimensions

KW12XQ25S1DO



Minimum outdoor unit clearances




Unit must be placed a minimim 18in (45cm) above any surfaces to allow for snow clearance and defrost runoff.

Please follow local best practices and guidelines.




Indoor unit specifications

Console		KM12XEDI		Net weight:	33 Lbs	Gross weight:	39.7 Lbs
Air flow volume		dB (A)			15.5 Kg		18.5 Kg
Turbo	441 CFM	750 m3/h	45	Included:	Infrared remote YBE1FB5F		
High	383 CFM	650 m3/h	42	Dehumidification level:		2.96 pt/hr	
Med-high	353 CFM	600 m3/h	40	Optional Accessories			
Medium	324 CFM	550 m3/h	38	24V interlock wired controller:		XE71-00/E	
Med-low	294 CFM	500 m3/h	37	Wired controller:		XE71-44G	
Low	365 CFM	450 m3/h	34	Embedded wired controller:		XE74-44E	
Sleep	206 CFM	350 m3/h	29	Embedded WIFI wired controller		XE72-44E	
Indoor unit Dimensions							



Minimum indoor unit clearances



Power supplied by outdoor unit

Additional Information

Connection method	Screwed
Liquid pipe	1/4in (6mm)
Gas pipe	3/8in (9.52mm)
Drain pipe (Outer Diameter)	1.1in (28mm)

Included Features

Wi-fi	Self Clean	8C heating	I-Feel	Soft start	Forced defrost
-------	------------	------------	--------	------------	----------------