



Submittal-48K-Ultranixx

Job name:		Submitted by:	
Location:		Submitted to:	
Engineer:		Unit tag:	
Date:		Drawing number:	

Warranty information

Standard 7 years parts & compressor
Registered 12 years parts & compressor
Terms and conditions apply

Type

Energy Star Heat Pump ☐

Cold Climate Energy Star Heat Pump ☒

Model numbers

Indoor:	KD48UXI
Outdoor:	KU60UXO

Capacity range

Output (BTU/H)	Minimum	Rated	Max	Certification		
Cooling:	34000	48000	50000	AHRI NO.	Energy Star	ne ep
Heating:	34000	48000	52000	217194946	4,011,419.	

Heating performance

Output (BTU/H)	Minimum	Rated	Max	Efficiency Ratings	
				SEER2	17
47F (8.3C)	15800	48000	48400	HSPF2	9.5
17F (-8.3C)	9800	39500	41500	EER (W/W)	3.3
5F (-15C)	18600	48000	48000	COP (W/W)	3.3

Outdoor temperature range

Cooling:	-15-54C	5-129F	Power supply	208-230V/60Hz/1Ph
Heating:	-30-24C	-22-75F	Min/Max voltage	187-253Vac

Condenser specifications

Connecting type	Screw Connection	MCA	39A
Pre-charge length	25ft (7.5M)	MOP	45A
MIN. Refrigerant Pipe Length	10 ft (3M)	Power Supply Wire	8/3 AWG
Liquid Pipe Size	3/8in (9.52mm)	Interconnecting Wire	18/6AWG or 18/2AWG

Gas Pipe Size	3/4in (19mm)	Features:	
Max Height Between Indoor/Outdoor	50ft (15M)	Electronic expansion valve	
Max. Pipe Length	100ft (30M)	Rotary compressor	
Refrigerant Type	R-32	Basepan heater	
Factory Charge	162oz	Compressor electric heater	

Additional Charge	0.3 oz/ft	Weight	
Sound Pressure Level	62dB (A)	Gross weight:	263.5Lbs (119.5Kg)
		Net weight:	241.4Lbs (109.5Kg)






Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.





Outdoor unit Dimensions

KU60UXO

Unit: Inch



Minimum outdoor unit clearances



Unit must be placed a minimum 18in (45cm) above any surfaces to allow for snow clearance and defrost runoff.

Please follow local best practices and guidelines.


Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.



Indoor unit specifics

KD48UXI

Unit: Inch



Technical Specifications	
Power Supply	208-230V/60Hz/1Ph
Sound pressure level	53dB(A)
MCA	7.1A
MOC	15A
Dehumidification	8.49 pt/hr
Net weight	199.5 lbs (90.5Kg)
Gross Weight	218 Lbs (99Kg)
Drain Pipe Outlet	SCH 40 3/4
*When there is no Electrical Heater installed There is no supplied Electrical breaker	
*If Electrical Heater is installed it will supply power to air handler	

Optional Smart thermostat	Electric Heater kits available					
WK-010WC01 and WK-010WD1	Model number	KW	MCA 240V	MCA 208V	MOC 240V	MOC 208V
* Metal mesh filter included	21-4216-03	10	52A	45A	60A	45A
20 5/8 x 20 5/16 x 1/2	21-4217-01	15	52A & 26A	45A & 22.6A	60A & 30A	45A & 25A
Fan Performance	21-4228-01	20	52A & 52A	45A & 45A	60A & 60A	45A & 45A

Level	Static pressure:inwg (Pa)											
	0 (0)	0.1 (25)	0.15 (37)	0.2 (50)	0.3 (75)	0.4 (100)	0.5 (125)	0.6 (150)	0.7 (175)	0.8 (200)	0.9 (225)	1 (250)
Speed 1(CFM)	1680	1560	1500	1350	-	-	-	-	-	-	-	-
Speed 2(CFM)	1810	1690	1620	1550	1380	-	-	-	-	-	-	-
Speed 3(CFM)	1930	1830	1770	1710	1580	1480	1200	-	-	-	-	-
Speed 4(CFM)	2280	2240	2200	2180	2130	2080	2000	1880	1750	1600	1400	1200
Speed 5(CFM)	2300	2260	2220	2190	2140	2090	2040	1980	1930	1800	1700	1550

Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.